



Power Delivery Charging Station - 65 W One USB-C Power Delivery Port up to 60 W, One USB-C Power Delivery

One USB-C Power Delivery Port up to 60 W, One USB-C Power Delivery Port up to 18 W, One Quick Charge™ Power Port up to 18 W, Black

Part No.: 102223

EAN-13: 0766623102223 | UPC: 766623102223

Power Delivery Charging Station - 65 W — Impressive device power

Enjoy complete charging power with the Manhattan Power Delivery Charging Station - 65 W. Its USB-C ports use PD technology to deliver the right amount of power to your laptop, smartphone, tablet or other compatible device at the fastest, safest rate. The additional USB-A port supports Qualcomm[®] Quick Charge™ technology to delivery up to 18 W of power to a compatible device. The perfect power companion with its stylish, compact and ultra-modern design, the Manhattan Power Delivery Charging Station - 65 W also smartly protects itself and your devices from short-circuits, overvoltage, overcurrent and overheating.

Features:

- Charging station solution with two USB-C Power Delivery (PD 3.0) and one Quick Charge™ USB-A charging ports
- Charges different devices simultaneously with optimized power allocation
- Total power output supported: 65 W
- One USB-C Power Delivery port delivering up to 60 W to charge a notebook, laptop, Ultrabook™, tablet or other USB-C powered device
- One USB-C PD port delivering up to 60 W
- One USB-C Power Delivery port delivering up to 18 W to charge a tablet, smartphone, game console or other USB-C powered device
- One USB-C PD port delivering up to 18 W
- One USB-A Quick Charge port delivering up to 18 W to charge any

manhattan° Life just got easier. **The control of the control of

manhattan-products.com

portable device

- One USB-A QC 3.0 port delivering up to 18 W
- · LED status indicator
- Overload, overcurrent and overheating protection
- Compact, portable and stylish design for easy travel
- Three-year warranty

Specifications:

Standards and Certifications

- USB
- Power Delivery 3.0
- Qualcomm® Quick Charge™ 3.0
- CE
- FCC
- RoHS
- WEEE
- ETL

Ports

- Two USB-C Power Delivery (PD 3.0)
- One USB-A Quick Charge 3.0

General

- AC input: 100 240 V; 50 60 Hz
- USB-C outputs: 5 20 V; maximum 3 A; 60 W
- Voltage/current settings (maximum):
- USB-C PD 60 W:
- -5V/3A
- -9V/3A
- 12 V / 3 A
- -15 V / 3 A
- 20 V / 3 A
- USB-C PD 18 W:
- -5V/3A
- -9 V / 2 A
- 12 V / 1.5 A
- USB-A QC 3.0 18 W:
- 3.6 6.5 V / 3 A
- 6.5 9 V / 2 A
- 9 12 V / 1.5 A

Input Characteristics

- AC rated voltage: 100 240 V
- Frequency range: 50 60 Hz (±1 Hz)
- Current: ≤ 1 A at 100 VAC 60 HZ



manhattan-products.com

Output Characteristics

• Rated voltage: 5 / 9 / 12 / 15 / 20 V

• Current: 3 A maximum (at constant voltage mode)

• Rated power: 72 watts maximum

• Overshoot voltage: ≤ 5%

Protection Characteristics

• Short-circuit (SCP) with auto-recovery mode

• Overvoltage (OVP) with auto-recovery mode

• Overcurrent (OCP) — current limit: 150% (max)

• Over-temperature (OTP)

Physical

• Dimensions: 7.2 x 11.8 x 1.95 cm (2.83 x 4.64 x 0.77 in.)

• Weight: 0.22 kg (7.76 oz.)

• Housing: plastic

Operating Environment

• Operation Temperature: 0 - 30°C (32 - 86°F)

• Storage Temperature: -20 - 65°C (-4 - 149°F)

• Humidity (noncondensing): 10 - 90%

Package Contents

• Power Delivery Charging Station - 65 W

• 1 m (3.3 ft.) Power cord

• 2 m (6 ft.) USB-C to USB-C cable, supports data transfer speeds of 480 Mbps

Instructions





manhattan-products.com







