


# T15m

Mini Size Optical Light Source



## Product Characteristics

- 2.5mm universal+SC adapter
- Typical output power:  $-5\text{dB}$
- Wavelength: 1310/1550nm
- Drop protection: 2m
- Low battery reminder function
- Water-resistant keys
- Pocket size design
- LED lighting, clear in the dark environment



Backlight display



One-key start



Automatic shutdown



Plug and play



Super long standby



Silicone protective case



## Main Features



Drop protection



Mini Size



LED lighting



Detachable protective sleeve



# T15m



Interface accessory



SC



FC



ST

Wavelength(nm)	1310/1550nm
Typical Output Power	-5dB
Optical Connector	SC+2.5mm universal+ (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(2 AAA 1.5V batteries)
Output Stability	±0.05dB/15mins; ±0.1dB/ 8hours
Modulation Frequencies	CW, 270Hz, 1KHz, 2KHz
Dimensions / Weight	130x65x35mm / 180g

## Product Display



### HEAD OFFICE

OrientTEK Optical Communication Ltd.

### CONTACT US

Huaqiao Building, Qinheng Technology Park, North Bridge road,  
Nanjing, Jiangsu, China  
TEL: + 86 25 8687 0518  
FAX: + 86 25 8687 0518  
[www.orientekot.com](http://www.orientekot.com)  
[sales@orientekot.com](mailto:sales@orientekot.com)

#### Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in China. In addition, the Export Administration Regulations (EAR) of the United States may be applicable. In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of China or the Department of Commerce of the United States for details about procedures.