

SmartCube 300W

Intelligent 3MP Wireless Cube IP Camera



3 Megapixel Wireless Cube IPCAM with PIR and Intelligence



3 Megapixel Resolution

10 times more resolution than standard VGA! SmartCube 300W can also work in 1080P Full HD and 720P resolutions.



PIR Sensor

Infrared Sensor that detects people and animals quickly and accurately for motion detection.



Built-in Audio and Speaker

Enable you for 2-way conversation through the IP Camera



Smart Video Intelligence

Camera can recognize faces, detect people, counting people, and set electronic fences.



Corridor Mode

Wide vertical viewing angle and less storage space for installation in corridor and aisles.



ICR Night Vision

Powerful IR LED for up to 15 meters distance in complete darkness



SD Card and Cloud Base Recording

Record video on SD Card and backup your video to the cloud. View the live video on your smartphones.

Specifications AirLive SmartCube 300W · AE, AW, BLC, WDR, 3DNR, Fog Compensation Camera Type Event Triggers • Brightness, Sharpness, Contrast, Saturation Motion detection • Wireless Cube iMotion Detection · Mirror/Flip, NTSC/PAL •Tamper Detection •Trip Zone Processor Privacy Masks •Periodically Time Object Counting •Text, time date image temperature and humidity OSD •SD Card Read/Write Fail •Face recognition •e-Fence •TI DMVA2 Detection Digital Zoom Network Disconnect System ROM •PIR Detection • Audio Detection •Temperature Detection •10x •128M byte NAND Flash • Face Detection Humidity Detection Intelligent Video Motion Detection •128M byte DDR SDRAM •Object Counting, Face Detection, Face Recognition, iMotion, Electronic fence Image Sensor Event handler •1/3" CMOS sensor •FTP, Samba Server, SD Push Notification Audio Encoder card file upload, Dropbox •HTTP and TCP notification •E-mail notice • Audio File Playback •G.711 •3MP (2048x1536) Audio Streaming UPnP Minimum Illumination •Two-wav • Yes •0.1 LUX (Color) Audio Input/Output Application Programming Interface Lens Type •Built-in speaker & microphone •Onvif Profile S •SDK •3.6 mm •Open API for software integration Video Buffer Viewing Angle Ethernet •Pre- and post- alarm buffering •95°(D) 64 °(H) 47 °(V) •Ethernet (10/100 Base-T), RJ-45 Wireless • Motion detection, Tamper Detection, Periodically •802.11n •10 IR LEDs Time, SD Card Read/Write Fail Detection, Network Disconnect, Audio Detection, Face Detection, Supported Protocols Max IR Distance iMotion Detection, Trip Zone, Object Counting, Face recognition, e-Fence, PIR Detection, Temperature •TCP/IP, IPV6, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, •15m FTP, HTTP, HTTPs, Samba, PPPoE, UPnP, Bonjour, RTP, Detection, Humidity Detection. Mechanical ICR RTSP, RTCP, DLNA, ISCSI, Onvif Profile S Continuous Recording • Yes Security PIR Sensor Password protection •IP filter, HTTPS encrypted data transmission OS Temperature Sensor • Windows VISTA / Windows XP / Windows 7/ Windows 8 •Up to 10 users simultaneous •Yes, 0 to 55° Celsius with + 5 degree margin of error •Internet Explorer (8.0+) / Chrome / Firefox / Safari Power LED •Yes, 0 to 90 percent with + 10% margin of error •Red Color Cell Phone Built-in Speaker AirLive APPCAM Link/Act, LED •Green Color/Flash Green Built-in Microphone •VLC, Quick Time, Real Player, Core Player •Blue Color SD Card Slot WPS/Reset Button Network Processor Micro SDXC • Push once to start WPS. Press and hold for 10 seconds to start factory reset •DSP Base Video Compression Softwar •1GB(Flash) •H.264 • MPEG-4 • MJPEG Android APP System RAM Video Profile Yes •2GB iOS APP Power Supply Yes Resolution and Frame Rate •DC 5V/1A Recording Software •20 fps @ 2048 X 1536 •30 fps @ 720 X 480 Power Consumption •Free PC Recording Software •30 fps @ 640 X 480 •30 fps @ 1920 X 1080 4 Watts Max. •30 fps @ 1280 x 1024 •30 fps @ 320 X 240 Mobile Web Wizard •30 fps @ 1280 X 720 •30fps @ 176 X 144 Connector Auto Detect and designed for smartphone •RJ-45 10BaseT/100BaseTX •DC 5V power jack and tablet PC Streaming •Streaming over UDP, TCP, or HTTP Environment PC Web Wizard 3GPP mobile view •Operation: Temp: -5°C ~ 55°C Humidity: 20% ~ 85% non-condensing Complete function settings · Configurable frame rate and bandwidth Support both CBR and VBR ONVIF •Storage: Temp: -15°C ~ 60°C Humidity: 0% ~ 90% non-condensing • Yes Region of Interest Search and Installation program Dimension AirLive IP Wizard II for Windows •H x W x D: 94 x 64 x 40 mm **Ordering Information:**

AirLive SmartCube 300W Intelligent 3MP Wireless Cube IP Camera